

# FutureCom™ Combi-Frame, 45 x 45 mm

white

CORNING

The LANscape® FutureCom™ combi-frame straight is suitable for the installation of LANscape FutureCom modules. The combi-frame 45 x 45 mm with self-closing shutters is intended for the direct assembly into cable raceways. Holders for cable tray are not intended, because the combi-frame can be in-clicked directly into the cable raceway. Two designation windows with designation stripes are included.

## Features

- Self-closing shutter
- Coding possibility with labeling icons for each port
- Designation window
- 45 x 45 mm footprint, e.g. compatible with Legrand "Mosaic"



## Specifications

### General Specifications

Halogen-free	Yes
Dust protection	Yes
Product category	Core product

### Design - Hardware

Number of ports	2
Colour	white, RAL 9010

### Mechanical Characteristics

Dimensions (L x W)	45 mm x 45 mm
--------------------	---------------

### Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	-----------------------------------------------------------

# FutureCom™ Combi-Frame, 45 x 45 mm

white



## Ordering Information

Part Number	CAXCSE-G0201-C011
Product Description	Combi-Frame 45 x 45 mm, with self-closing shutters for the installation of 2 FutureCom™ modules, straight, designation window and coding possibility *Not suited for connectors requiring the FutureCom Adapter or LANS/LANC adapter modules (S1200 Connector, Fiber Optic Adapters)
EAN Code	4042673241225
Weight	8 g

## Shipping Information

Units per delivery	1/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.